

HONGFA UEB1-70 SERIES MINIATURE CIRCUIT BREAKER (MCB)



The UEB1-70 series Miniature Circuit Breaker (MCB) has the following features:

- Mechanical Switch to manually disconnect the circuit.
- ON/OFF Display Indicator (INDI-ON)
- Common trip for all poles.
- Surface-Flush Mount, and DIN Rail Mount.
- Operate in all mounting positions.
- I/O Lug Standard Termination.

UEB1-70 MCB Table 1 MCB

Product Features	Approval	UL489	
	Number of Poles	1P, 2P, 3P	
	Mounting Type	DIN-rail, Surface-Flush	
	Wiring connection terminal	Box lug: QC terminal	
	Rated parameters	A. Rated voltage: 120/240Vac, 240Vac	
		B. Rated current: 5, 10, 15, 20, 25, 30, 35, 40, 45, 50, 60A	
		C. Rated frequency: 50/60Hz	
		D. Rated Insulated Voltage: 690Vac	
	Short Circuit Rating	10kA	
	Application life	10000 cycles	
	A. Mechanical B. Electrical	10000 cycles 6000 cycles	
	Operation Temperature	-10°C ~ 60°C (14°F ~ 140°F)	
	Storage Temperature	-40°C ~ +70°C (-40°F ~ 158°F)	
Relative Humidity	90-95%RH (below 40°C/104°F)		
Altitude	≤200M (6562 feet)		